



06-12-00

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

ATTY DOCKET NO.: 9040.7

DATE: June 9, 2000

UTILITY PATENT APPLICATION TRANSMITTAL LETTER
AND FEE TRANSMITTAL FORM (37 CFR 1.53(b))

BOX PATENT APPLICATION

Director for Patents and Trademarks

Washington, DC 20231

Sir:

Transmitted herewith for filing under 37 CFR 1.53(b) is:

- ☒ a patent application
☐ a Continuation ☐ a Divisional ☐ a Continuation-in-Part (CIP)

of prior application no.: ; filed .

- ☐ A Small Entity Statement(s) was filed in the prior application; Status still proper and desired.

Inventor(s) or Application Identifier:

Thomas Boucino, Hickory, North CarolinaEntitled: **Communications Cable with Isolators**

Enclosed are:

1. ☒ Application Transmittal Letter and Fee Transmittal Form (*A duplicate is enclosed for fee processing*)
2. ☒ 24 pages of Specification (including 45 claims)
3. ☒ 8 sheets of Formal Drawings (35 USC 113)
4. ☐ Oath or Declaration
 - a. ☐ newly executed (*original or copy*)
 - b. ☐ copy from prior application (37 CFR 1.63(d) (*for continuation/divisional*) [Note Box 5 Below])
 - c. ☐ **DELETION OF INVENTOR(S)** (*Signed statement deleting inventor(s) named in the prior application*)
5. ☐ Incorporation By Reference (*useable if box 4b is checked*)

The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
6. ☐ Microfiche Computer Program (*Appendix*)
7. ☐ Assignment papers (*cover sheet(s) and document(s)*)
8. ☐ Small Entity Statement(s)
9. ☐ Information Disclosure Statement, PTO-1449, and references cited
10. ☐ Preliminary Amendment (*Please enter all claim amendments prior to calculating the filing fee.*)
11. ☐ English Translation Document
12. ☐ Certified Copy of

13. ☐ Sequence Listing/ Sequence Listing Diskette
a. ☐ computer readable copy
b. ☐ paper copy
c. ☐ statement in support
14. ☐ An Associate Power of Attorney
15. ☒ Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
16. ☒ Other: Application Filed Under 37 CFR 1.41(c)

The fee has been calculated as shown below:

	Column 1 No. Filed	Column 2 No. Extra	Small Entity Rate Fee	Large Entity Rate Fee
BASIC FEE			\$345.00	\$690.00
TOTAL CLAIMS	45 - 20 =	25	x 09 = \$	x 18 = \$450.00
INDEP CLAIMS	9 - 3 =	6	x 39 = \$	x 78 = \$468.00
<input type="checkbox"/> MULTIPLE Dependent Claims Presented			+ 130 = \$	+ 260 = \$
If the difference in Col. 1 is less than zero, Enter "0" in Col. 2			Total \$	Total \$1608.00

☒ A check in the amount of \$1608.00 to cover the filing fee is enclosed.


☐ A check in the amount of \$ _____ is enclosed to cover the filing fee, PLUS the Assignment Recordation fee (\$40.00).

☒ The Commissioner is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to Deposit Account No. 50-0220.

☒ Any additional filing fees required under 37 CFR 1.16.

☒ Any patent application processing fees under 37 CFR 1.17.

Respectfully submitted,



Mitchell S. Bigel
Registration No. 29,614

Correspondence Address:
USPTO Customer Number: **20792**
Myers Bigel Sibley & Sajovec
Post Office Box 37428
Raleigh, North Carolina 27627
Telephone (919) 854-1400
Facsimile (919) 854-1401

CERTIFICATE OF EXPRESS MAILING

Express Mail Label No. EL481791387US
Date of Deposit: June 9, 2000

I hereby certify that this correspondence is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to Box Patent Application, Director For Patents and Trademarks, Washington, DC 20231.


Vickie Diane Prior
Date of Signature: June 9, 2000

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re: Thomas Boucino
Serial No.: To Be Assigned
Filed: Concurrently Herewith
For: COMMUNICATIONS CABLES WITH ISOLATORS

June 9, 2000


Box Patent Application
Director for Patents and Trademarks
Washington, DC 20231

APPLICATION FILED UNDER 37 CFR 1.41(c)

Sir:

The above-identified application is being filed on behalf of the inventor,
Thomas Boucino, under the provisions of 37 CFR 1.41(c). A Declaration and Power of
Attorney from the inventor will follow, 37 CFR 1.63.

Respectfully submitted,



Mitchell S. Bigel
Registration No. 29,614

USPTO Customer No. 20792
Myers Bigel Sibley & Sajovec
Post Office Box 37428
Raleigh, North Carolina 27627
Telephone (919) 854-1400
Facsimile (919) 854-1401

CERTIFICATE OF EXPRESS MAILING

"Express Mail" mailing label number EL481791387US
Date of Deposit: June 9, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. 1.10 on the date indicated above and is addressed to Box Patent Application, Director for Patents and Trademarks, Washington, DC 20231.


Vickie Diane Prior
Date of Signature: June 9, 2000



COMMUNICATIONS CABLES WITH ISOLATORS

Field of the Invention

The present invention relates broadly to communications cable and more particularly, to communications cable containing at least one twisted pair of
5 insulated conductors.

Background of the Invention

Insulated conductors such as those used in communications cable are often provided as twisted pairs of insulated conductors having two insulated conductors
10 twisted about each other to form a two conductor group. A typical assembly for these communications cables comprises two or more twisted pairs of insulated conductors bundled together and contained in a cable jacket. This assembly can facilitate the installation of the cable. In addition, the cable can be connected to other cable components by stripping the cable jacket and making the proper
15 connections between the insulated conductors.

One problem associated with communications cable produced with the conventional twisted pair assembly is that crosstalk can occur between twisted pairs of insulated conductors that can negatively affect the signals transmitted by these conductors. Crosstalk may especially present a problem in high frequency
20 applications because crosstalk may increase logarithmically as the frequency of the transmission increases. Because crosstalk is affected to some degree by the distance between twisted pairs of insulated conductors, one method of reducing its occurrence is to space the twisted pairs of insulated conductors apart using a spacing means. An example of such spacing means can be found in U.S. Patent
25 No. 5,789,711 to Gaeris et al. which discloses a high performance data cable which has an interior support or star separator. Another example of such a spacing means can be found in U.S. Patent No. 5,969,295 to the present inventor Boucino, et al., ("the '295 patent") which discloses a communications cable that includes a cable

jacket, twisted pairs of insulated conductors, and a spacer separating the twisted pairs of insulated conductors. The spacer in the '295 patent extends within the cable jacket and has a longitudinally extending center portion and a plurality of wall portions radiating from the center portion thereby defining a plurality of compartments within the cable jacket.

Summary of the Invention

According to embodiments of the present invention, communications cables are provided which utilize a cable jacket, twisted pairs of insulated conductors, and a spacer separating the twisted pairs of insulated conductors. The spacer extends within the cable jacket and has a longitudinally extending center portion and a plurality of wall portions radiating from the center portion thereby defining a plurality of compartments within the cable jacket. In various embodiments of the present invention, the plurality of wall portions include a plurality of radiating sections with varying geometric shapes. The twisted pairs of insulated conductors are disposed in the compartments.

In embodiments of the present invention, communications cables include a cable jacket, a spacer extending within the cable jacket and having a longitudinally extending center portion and plurality of longitudinally extending wall portions radiating from the center portion that increase in thickness from the center portion to the cable jacket. The spacer and the cable jacket define a plurality of compartments within the cable jacket. One or more twisted pairs of insulated conductors are disposed in one or more of the plurality of compartments. The communications cable may also have a shield extending between the spacer and the cable jacket. The twisted pairs of insulated conductors may each have a different lay length. The plurality of longitudinally extending wall portions may be configured so as to define a plurality of compartments of a helical configuration within the cable jacket and the plurality of twisted pairs of insulated conductors located within the plurality of compartments may extend helically about the longitudinal axis of the cable.

In other embodiments of the present invention, the plurality of longitudinally extending wall portions may increase in thickness over only a portion thereof from the center portion to the cable jacket.

In further embodiments of the present invention, the plurality of longitudinally extending wall portions may decrease in thickness over only a portion thereof from the center portion to the cable jacket.

In still further embodiments of the present invention, the longitudinally
5 extending wall portions have a first radial section that increases in thickness with distance from the center portion and a second radial section that decreases in thickness with distance from the center portion. The first radial section may be located between the center portion and the second radial section or the second radial section may be located between the center portion and the first radial
10 section. The first radial section and the second radial section may be configured such that the plurality of longitudinally extending wall portions have a convex shaped cross-section that may be arcuate and/or include a plurality of faces. The first radial section and the second radial section may also be configured such that the plurality of longitudinally extending wall portions have a concave shaped
15 cross-section that may be arcuate and/or include a plurality of faces. The first radial section and second radial section may further be configured such that the plurality of longitudinally extending wall portions have a recessed portion and/or a ribbed portion.

In still other embodiments of the present invention, the longitudinally
20 extending wall portions may have a first section having a first thickness, a second section having a second thickness and a third section having a third thickness and located between the first section and the second section. The third thickness is different from the first and second thickness. In one embodiment, the first thickness, the second thickness and the thickness of the third section are all
25 different. In another embodiment, the first thickness and the second thickness may be the same and the third thickness may be either thicker or thinner than the first thickness.

In still further embodiments of the present invention, the longitudinally
30 extending wall portions may have a sawtooth shaped cross-section having a plurality of teeth. Each tooth may have a tooth height and a tooth spacing. In one embodiment, each tooth height is the same. In other embodiments, at least two tooth heights are different. In yet other embodiments, each tooth spacing is the same. In still other embodiments, at least two tooth spacings are different. In

other embodiments, at least two tooth heights are different and at least two tooth spacings are different

In still other embodiments of the present invention, the longitudinally extending wall portions may have a first radial section and a second radial section having a knob shaped cross-section. The knob shaped cross-section may be any portion of a knob including a half knob and/or a whole knob.

Brief Description of the Drawings

Figure 1 is a perspective view of embodiments of communications cables of the present invention;

Figure 2 is a cross-sectional view of communications cables of **Figure 1** taken along line 2-2;

Figure 3 is a cross-sectional view of other embodiments of communications cables according to the present invention.

Figure 4 is a cross-sectional view of further embodiments of communications cables according to the present invention.

Figure 5 is a cross-sectional view of still other embodiments of communications cables according to the present invention.

Figure 6 is a cross-sectional view of still further embodiments of communications cables according to the present invention.

Figure 7 is a cross-sectional view of still other embodiments of communications cables according to the present invention.

Figure 8 is a cross-sectional view of still further embodiments of communications cables according to the present invention.

Detailed Description of the Preferred Embodiments

The present invention now will be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein. Instead, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. It will be understood that when an element (e.g., cable jacket) is referred to as being "connected to" another element, it can be directly connected to the other

element or intervening elements may also be present. In contrast, when an element is referred to as being "directly connected to" another element, there are no intervening elements present. Like numbers refer to like elements throughout.

Referring now to **Figures 1 and 2**, embodiments of communications cables according to the present invention will now be described. The illustrated communications cable **10** includes a cable jacket **12**, a spacer **14**, a plurality of twisted pairs of insulated conductors **20, 22, 24, 26**, a shield **16** and a plurality of compartments **40, 42, 44, 46**. The cable jacket **12** surrounds the spacer **14**, the shield **16** and the twisted pairs **20, 22, 24, 26** and is preferably tubular in shape. Preferably, the cable jacket **12** is made of a flexible polymer material and is formed by melt extrusion. As will be understood by those of skill in the art, any of the polymer materials conventionally used in cable construction may be suitably employed including, but not limited to, polyvinylchloride, polyvinylchloride alloys, polyethylene, polypropylene and flame retardant materials such as fluorinated polymers. Moreover, other materials and/or fabrication methods may be used. Preferably, the cable jacket **12** is extruded to a thickness of between 15 and 25 mils (thousandths of an inch) which may facilitate stripping the cable jacket **12** away from the twisted pairs **20, 22, 24, 26**. However, other dimensions may be used.

With reference to **Figure 1**, the shield **16** is located between the spacer **14** and the cable jacket **12** and is preferably longitudinally coextensive with the cable jacket **12**. The shield **16** may be made from a wide variety of known conductive and/or nonconductive materials such as nonconductive polymeric tape; conductive tape; braid; a combination of nonconductive polymeric tape, conductive tape and/or braid; and/or other such materials as will be understood to one of skill in the art using conventional fabrication techniques. The shield **16** may include one or more layers of material **16a, 16b** and may be applied longitudinally, helically, etc. and/or may be braided as will be understood to one of skill in the art. As will be understood by one of skill in the art, the shield **16** can be omitted from the communications cable **10**.

As shown in **Figure 1**, the spacer **14** is situated within and is longitudinally coextensive with the cable jacket **12**. As illustrated in **Figure 2**, the spacer **14** includes a longitudinally extending center portion **30** and a plurality of longitudinally extending wall portions **32, 34, 36, 38** radiating from the center

portion **30**. As illustrated in **Figure 2**, the wall portions **32, 34, 36, 38** preferably increase in thickness from the center portion **30** to the cable jacket **12**. The spacer **14** and the cable jacket **12** may define a plurality of compartments **40, 42, 44, 46** in which the twisted pairs **20, 22, 24, 26** may be located. Alternatively, the plurality of compartments may be defined by the spacer **14** and the shield **16**. Each of the compartments **40, 42, 44, 46** is preferably of sufficient size to receive a corresponding twisted pair **20, 22, 24, 26**. The communications cable **10** preferably has at least four compartments **40, 42, 44, 46** to receive at least four respective twisted pairs **20, 22, 24, 26**. Although the illustrated communications cable **10** has four compartments **40, 42, 44, 46** which can receive four twisted pairs **20, 22, 24, 26**, it will be understood by those skilled in the art that the communications cable **10** may have two, three, four or more compartments **40, 42, 44, 46** for receiving a plurality of twisted pairs **20, 22, 24, 26** and that every compartment **40, 42, 44, 46** need not include a twisted pair **20, 22, 24, 26**.

As shown in **Figure 1**, the insulated conductors **27** of each twisted pair **20, 22, 24, 26** are twisted helically around one another. Preferably, the twisted pairs **20, 22, 24, 26** are typically twisted at a lay length of between about 0.25 and about 1.50 inches and each of the twisted pairs **20, 22, 24, 26** preferably has a different lay length from any other twisted pair **20, 22, 24, 26** of the communications cable **10**.

As shown in **Figure 1** with reference to only one twisted pair **24** for purposes of illustration, each insulated conductor **27** in the twisted pair **24** comprises a conductor **28** surrounded by a layer of an insulated material **29**. The conductor **28** may be a metallic wire of any of the well-known metallic conductors used in wire and cable applications, such as copper, aluminum, copper-clad aluminum and/or copper-clad steel. Preferably, the wire is 18 to 26 AWG gauge. The conductor **28** is surrounded by a layer of the insulating material **29**. Preferably, the thickness of the insulating material **29** is less than about 25 mil, preferably less than about 15 mil, and for certain applications even less than about 10 mil. The insulating material **29** may also be foamed or expanded through the use of a blowing or foaming agent. Suitable insulating materials for the insulated conductor **27** include polyvinylchloride, polyvinylchloride alloys, polyethylene, polypropylene, and flame retardant materials such as fluorinated polymers. Exemplary fluorinated polymers for use in the invention include fluorinated

ethylene-propylene (FEP), ethylenetrifluoroethylene (ETFE), ethylene chlorotrifluoroethylene (ECTFE), perfluoroalkoxypolymers (PFA's), and mixtures thereof. Exemplary PFA's include copolymers of tetrafluoroethylene and perfluoropropylvinylether (*e.g.*, Teflon PFA 340) and copolymers of

5 tetrafluoroethylene and perfluoromethylvinylether (MFA copolymers which are available from Ausimont S.p.A.). In addition, the insulating material **29** can contain conventional additives such as pigments, nucleating agents, thermal stabilizers, acid acceptors, processing aids, and/or flame retardant compositions (*e.g.*, antimony oxide). If desired, the insulating material **29** used for the insulated

10 conductor **27** may not be the same for each twisted pair **20, 22, 24, 26**. For example, three of the twisted pairs **20, 22, 24, 26** may be constructed using a foamed polyvinylchloride insulating material **29** while the fourth twisted pair **20, 22, 24, 26** is constructed using a different insulating material **29** such as a foamed FEP. Other materials, dimensions and/or fabrication techniques for the conductors

15 and/or insulating materials **29** may be used.

As shown in **Figure 1**, the wall portions **32, 34, 36, 38** of the communications cable **10** may be configured so as to define longitudinally extending passageways or compartments **40, 42, 44, 46** of a helical configuration within the cable jacket **12** so that the respective twisted pairs **20, 22, 24, 26** located

20 within the compartments **40, 42, 44, 46** extend helically around the longitudinal axis of the communications cable **10**. Typically, the spacer **14** and the twisted pairs **20, 22, 24, 26** are twisted to provide this helical configuration thereby holding these cable components together. Furthermore, this helical configuration may improve the impedance uniformity of the cable by maintaining uniformity of

25 spacing of the respective twisted pairs **20, 22, 24, 26** despite bending of the communications cable **10**. The cable components may be twisted helically at a predetermined lay length defined as the length it takes for one of the cable components (*e.g.*, one twisted pair **20, 22, 24, 26**) to make one complete helical turn. Preferably, the lay length is between about 3 and about 8 inches. However,

30 other lay lengths may be used.

Figures 1 and 2 illustrate embodiments of the invention wherein the spacer **14** is separate from the shield **16**. In this configuration, the wall portions **32, 34, 36, 38** radiate from the center portion **30** and terminate proximate to the shield **16**. The communications cable **10** illustrated in **Figures 1 and 2** may be manufactured

by extruding the spacer **14** using a suitable polymer material, such as the materials described above for use in the cable jacket **12**. The spacer **14** may also comprise conductors such as metal and/or semiconductors such as carbon. The spacer **14** may be formed into a desired shape as it exits the extruder and is cooled or quenched to harden the spacer **14**. The spacer **14** may then be bunched with four twisted pairs **20, 22, 24, 26** such that the twisted pairs **20, 22, 24, 26** are oriented in the compartments **40, 42, 44, 46** of the spacer **14**. The spacer **14** and the twisted pairs **20, 22, 24, 26** may also be twisted helically during the bunching process which may increase the impedance uniformity of the communications cable **10**. Once the spacer **14** and the twisted pairs **20, 22, 24, 26** are bunched, the shield **16** may be applied and the cable jacket **12** may then be extruded around the shield **16**, spacer **14** and twisted pairs **20, 22, 24, 26** to form the communications cable **10**. Other manufacturing techniques may also be used.

Although the spacer **14** of the embodiment of **Figures 1 and 2** is not connected to the shield **16**, the wall portions **32, 34, 36, 38** of the spacer **14** may be connected to the shield **16**. The spacer **14** may be connected to the shield **16**, for example, by designing the spacer **14** so that it extends slightly beyond the twisted pairs **20, 22, 24, 26** and constructing the shield **16** from heat bonded foil tape which, when heated through the cable jacket extrusion process, may become bonded to the spacer **14**. Other manufacturing techniques may also be used.

As mentioned above, the shield **16** may be omitted from the communications cable **10**. Techniques from manufacturing a communications cable without a shield, but with the spacer either connected or not connected to the cable jacket, are disclosed in U. S. Patent No. 5,969,295 to the present inventor Boucino, et al., entitled "Twisted Pair Communications Cable," which patent is hereby incorporated by reference as if fully set forth herein.

With reference to **Figure 3**, a communications cable **110** according to further embodiments of the present invention will now be described. The communications cable **110** includes a cable jacket **112**, a spacer **114**, a plurality of twisted pairs of insulated conductors **120, 122, 124, 126**, a shield **116** and a plurality of compartments **140, 142, 144, 146**. It will, however, be understood that the shield **116** may be omitted. The cable jacket **112**, the plurality of twisted pairs of insulated conductors **120, 122, 124, 126**, the shield **116** and the plurality of compartments **140, 142, 144, 146** may generally be constructed in the same

manner as the cable jacket **10**, the plurality of twisted pairs of insulated conductors **20, 22, 24, 26**, the shield **16** and the plurality of compartments **40, 42, 44, 46** described above with reference to the communications cable **10**. Accordingly, a detailed description thereof need not be repeated.

As shown in **Figure 3**, the spacer **114** is situated within and is longitudinally coextensive with the cable jacket **112**. The spacer **114** may comprise the same materials and may be fabricated using the same fabrication techniques that were discussed in connection with the spacer **14**. As illustrated in **Figure 3**, the spacer **114** includes a longitudinally extending center portion **130** and a plurality of longitudinally extending wall portions **132, 134, 136, 138** radiating from the center portion **130**. Each individual wall portion **132, 134, 136, 138** preferably includes a plurality of radial sections **138a, 138b** wherein each individual radial section **138a, 138b** may be of constant thickness, or may increase in thickness or decrease in thickness with distance from the center portion **130**. As will be understood to one of skill in the art, the change in thickness of the radial sections that increase or decrease in thickness may be linear or non-linear, and may be continuous or discontinuous. In the embodiment illustrated in **Figure 3**, each wall portion **132, 134, 136, 138** includes two radial sections **138a, 138b** that are configured such that the wall portions **132, 134, 136, 138** first decrease in thickness with distance from the center portion **130** and then increase in thickness with distance from the center portion **130**. As used herein, the term "configured" refers to the shape of a radial section **138a, 138b** and/or the location of the radial sections **138a, 138b** relative to one another.

As will be understood to one of skill in the art, the plurality of radial sections **138a, 138b** may be configured to produce wall portions **132, 134, 136, 138** with a wide variety of shapes including, but not limited to, configurations where the wall portions **132, 134, 136, 138** first decrease in thickness with distance from the center portion **130** and then increase in thickness with distance from the center portion **130**, configurations where the wall portions **132, 134, 136, 138** increase in thickness over only a portion thereof with the remaining portion being of constant thickness, and configurations where the wall portions **132, 134, 136, 138** decrease in thickness over only a portion thereof with remaining portion being of constant thickness. As will be understood to one of skill in the art, two or more radial sections **138a, 138b** can be used. These embodiments may allow for better

control of the location of the twisted pairs within the compartments which may provide better separation between the twisted pairs which may, in turn, improve crosstalk performance at the possible expense of decreasing the flexibility of the cable, which may depend on the amount of material used in the center portion, and increasing the possibility that the wall portions may fold over against the twisted pairs which may adversely affect the impedance and return loss. These embodiments may also provide increased surface contact between the spacer and the cable jacket or, if included, the shield, which may better protect the twisted pairs during the process of stripping the cable jacket and/or shield away.

With reference to **Figure 4**, a communications cable **210** according to further embodiments of the present invention will now be described. The communications cable **210** includes a cable jacket **212**, a spacer **214**, a plurality of twisted pairs of insulated conductors **220, 222, 224, 226**, a shield **216** and a plurality of compartments **240, 242, 244, 246**. It will, however, be understood that the shield **216** may be omitted. The cable jacket **212**, the plurality of twisted pairs of insulated conductors **220, 222, 224, 226**, the shield **216** and the plurality of compartments **240, 242, 244, 246** may generally be constructed in the same manner as the cable jacket **10**, the plurality of twisted pairs of insulated conductors **20, 22, 24, 26**, the shield **16** and the plurality of compartments **40, 42, 44, 46** described above with reference to the communications cable **10**. Accordingly, a detailed description thereof need not be repeated.

As shown in **Figure 4**, the spacer **214** is situated within and is longitudinally coextensive with the cable jacket **212**. The spacer **214** may comprise the same materials and may be fabricated using the same fabrication techniques that were discussed in connection with the spacer **14**. As illustrated in **Figure 4**, the spacer **214** includes a longitudinally extending center portion **230** and a plurality of longitudinally extending wall portions **232, 234, 236, 238** radiating from the center portion **230**. Each individual wall portion **232, 234, 236, 238** preferably includes plurality of radial sections **238a, 238b** wherein each individual radial section **238a, 238b** may be of constant thickness, or may increase in thickness or decrease in thickness with distance from the center portion **230**. As will be understood to one of skill in the art, the change in thickness of the radial sections that increase or decrease in thickness may be linear or non-linear, and may be continuous or discontinuous. In the embodiment illustrated in **Figure 4**, each

wall portion **232, 234, 236, 238** includes two radial sections **238a, 238b** which are configured such that the wall portions **232, 234, 236, 238** have a convex shaped cross-section.

As will be understood by one of skill in the art, the plurality of radial sections **238a, 238b** may also be configured to produce wall portions **232, 234, 236, 238** with a wide variety cross-sectional shapes including, but not limited to, configurations that have a concave shaped cross-section and configurations that have a cross-section that alternates between convex shaped and concave shaped. As will also be understood by one of skill in the art, the convex and concave cross-sections may be arcuate in shape or may be formed from a plurality of faces. As will be understood to one of skill in the art, two or more radial sections **238a, 238b** can be used. These embodiments may allow for better control of the location of the twisted pairs within the compartments which may provide better separation between the twisted pairs which may, in turn, improve crosstalk performance at the possible expense of requiring more material which may increase manufacturing cost and may decrease cable flexibility. These embodiments may also be easier to manufacture.

With reference to **Figure 5**, a communications cable **310** according to further embodiments of the present invention will now be described. The communications cable **310** includes a cable jacket **312**, a spacer **314**, a plurality of twisted pairs of insulated conductors **320, 322, 324, 326**, a shield **316** and a plurality of compartments **340, 342, 344, 346**. It will, however, be understood that the shield **316** may be omitted. The cable jacket **312**, the plurality of twisted pairs of insulated conductors **320, 322, 324, 326**, the shield **316** and the plurality of compartments **340, 342, 344, 346** may generally be constructed in the same manner as the cable jacket **10**, the plurality of twisted pairs of insulated conductors **20, 22, 24, 26**, the shield **16** and the plurality of compartments **40, 42, 44, 46** described above with reference to the communications cable **10**. Accordingly, a detailed description thereof need not be repeated.

As shown in **Figure 5**, the spacer **314** is situated within and is longitudinally coextensive with the cable jacket **312**. The spacer **314** may comprise the same materials and may be fabricated using the same fabrication techniques that were discussed in connection with the spacer **14**. As illustrated in **Figure 5**, the spacer **314** includes a longitudinally extending center portion **330**

and a plurality of longitudinally extending wall portions **332, 334, 336, 338** radiating from the center portion **330**. Each individual wall portion **332, 334, 336, 338** preferably includes a plurality of radial sections **338a, 338b . . . 338n** wherein each individual radial section **338a, 338b . . . 338n** may be of constant thickness, or may increase in thickness or decrease in thickness with distance from the center portion **330**. As will be understood to one of skill in the art, the change in thickness of the radial sections that increase or decrease in thickness may be linear or non-linear, and may be continuous or discontinuous.

In the embodiment illustrated in **Figure 5**, the plurality of radial sections **338a, 338b . . . 338n** are configured such that the wall portions **332, 334, 336, 338** have a saw-toothed shaped cross-section wherein each individual tooth has a height **X, Y** and the teeth are spaced at a distance **E, F**. As will be understood by one of skill in the art, the height **X, Y** of each individual tooth may be equal to or may vary from the height **X, Y** of any other tooth and the distance **E, F** between teeth may be equal to or may vary from the distance **E, F** between any two other teeth. It will also be understood that the number of teeth may vary from the number shown in **Figure 5**, and that the number of teeth may vary between wall portions **332, 334, 336, 338**. These embodiments may allow for better control of the location of the twisted pairs within the compartments which may provide better separation between the twisted pairs which, in turn, may improve crosstalk performance. Additionally, these embodiments may produce a more flexible cable due to the possible accordion affect that may take place within the wall portions, all at the possible expense of adversely affecting manufacturing stability and possibly creating pinch points on the twisted pairs which may degrade impedance and return loss performance.

With reference to **Figure 6**, a communications cable **410** according to further embodiments of the present invention will now be described. The communications cable **410** includes a cable jacket **412**, a spacer **414**, a plurality of twisted pairs of insulated conductors **420, 422, 424, 426**, a shield **416** and a plurality of compartments **440, 442, 444, 446**. It will, however, be understood that the shield **416** may be omitted. The cable jacket **412**, the plurality of twisted pairs of insulated conductors **420, 422, 424, 426**, the shield **416** and the plurality of compartments **440, 442, 444, 446** may generally be constructed in the same manner as the cable jacket **10**, the plurality of twisted pairs of insulated conductors

20, 22, 24, 26, the shield **16** and the plurality of compartments **40, 42, 44, 46** described above with reference to the communications cable **10**. Accordingly, a detailed description thereof need not be repeated.

As shown in **Figure 6**, the spacer **414** is situated within and is
 5 longitudinally coextensive with the cable jacket **412**. The spacer **414** may comprise the same materials and may be fabricated using the same fabrication techniques that were discussed in connection with the spacer **14**. As illustrated in **Figure 6**, the spacer **414** includes a longitudinally extending center portion **430** and a plurality of longitudinally extending wall portions **432, 434, 436, 438**
 10 radiating from the center portion **430**. Each individual wall portion **432, 434, 436, 438** preferably includes plurality of radial sections **438a, 438b** wherein each individual radial section **438a, 438b** may be of constant thickness, may increase in thickness or decrease in thickness with distance from the center portion **430**, or may have a knob shaped cross-section. As will be understood to one of skill in the
 15 art, the change in thickness of the radial sections that increase or decrease in thickness may be linear or non-linear, and may be continuous or discontinuous. In the embodiment illustrated in **Figure 6**, each wall portion **432, 434, 436, 438** includes two radial sections **438a, 438b** with the first radial section **438a** being of constant thickness and the second radial section **438b** having a knob shaped cross-section and a size **G, H, I, J**. Although the knob shaped radial section in **Figure 6**
 20 is a whole knob, one of skill in the art will understand that the knob shaped radial section may consist of only a portion of a knob including a half knob and that the size **G, H, I, J** of a knob may be the same or may vary between knobs.

As will be also understood by one of skill in the art, the plurality of radial
 25 sections **438a, 438b** may also be configured to produce wall portions **432, 434, 436, 438** with a wide variety of shapes including, but not limited to, configurations that include multiple knob shaped radial sections and configurations that include knob shaped radial sections combined with radial sections that increase in thickness and/or radial sections that decrease in thickness and/or radial sections of
 30 constant thickness. It will also be understood that the knobs need not be at the ends of the spacer. These embodiments may restrain the twisted pairs from becoming too close to the cable jacket which may make the cable easier to manufacture at the possible expense of allowing the twisted pairs to move closer together which may decrease crosstalk performance. These embodiments may also

provide increased surface contact between the spacer and the cable jacket or, if included, the shield, which may better protect the twisted pairs during the process of stripping the cable jacket and/or shield away, and may reduce the possibility that the twisted pairs will slip out of their respective compartments during
5 manufacturing which may increase the stability of the cable.

With reference to **Figure 7**, a communications cable **510** according to further embodiments of the present invention will now be described. The communications cable **510** includes a cable jacket **512**, a spacer **514**, a plurality of twisted pairs of insulated conductors **520**, **522**, **524**, **526**, a shield **516** and a
10 plurality of compartments **540**, **542**, **544**, **546**. It will, however, be understood that the shield **516** may be omitted. The cable jacket **512**, the plurality of twisted pairs of insulated conductors **520**, **522**, **524**, **526**, the shield **516** and the plurality of compartments **540**, **542**, **544**, **546** may generally be constructed in the same manner as the cable jacket **10**, the plurality of twisted pairs of insulated conductors
15 **20**, **22**, **24**, **26**, the shield **16** and the plurality of compartments **40**, **42**, **44**, **46** described above with reference to the communications cable **10**. Accordingly, a detailed description thereof need not be repeated.

As shown in **Figure 7**, the spacer **514** is situated within and is longitudinally coextensive with the cable jacket **512**. The spacer **514** may
20 comprise the same materials and may be fabricated using the same fabrication techniques that were discussed in connection with the spacer **14**. As illustrated in **Figure 7**, the spacer **514** includes a longitudinally extending center portion **530** and a plurality of longitudinally extending wall portions **532**, **534**, **536**, **538** radiating from the center portion **530**. Each individual wall portion **532**, **534**, **536**,
25 **538** preferably includes plurality of radial sections **538a**, **538b**, **538c** wherein each individual radial section **538a**, **538b**, **538c** may be of constant thickness, or may increase in thickness or decrease in thickness with distance from the center portion **530**. As will be understood to one of skill in the art, the change in thickness of the radial sections that increase or decrease in thickness may be linear or non-linear,
30 and may be continuous or discontinuous. In the embodiment illustrated in **Figure 7**, each wall portion **532**, **534**, **536**, **538** includes three radial sections **538a**, **538b**, **538c** which are configured such that the middle radial section **538b** is thicker than the other two radial sections **538a**, **538c** thus forming a ribbed portion. Alternatively, the embodiment illustrated in **Figure 7** may also be described as

including two radial sections **538d**, **538e**, one that increases in thickness in a discontinuous manner **538d** with distance from the center portion **530** and one that decreases in thickness in a discontinuous manner **538e** with distance from the center portion **530**, which are configured such that the wall portions **532**, **534**, **536**,
5 **538** have a ribbed portion.

As will be understood by one of skill in the art, the width **B** of a ribbed portion for any one wall portion **532**, **534**, **536**, **538** may be the same as or may vary from the width **B** of a ribbed portion for any other wall portion **532**, **534**, **536**, **538**. It will also be understood that there may be multiple ribbed portions. These
10 embodiments may increase twisted pair separation by increasing the thickness of the wall portions located adjacent to the twisted pairs which may improve crosstalk performance at the possible expense of moving the twisted pairs undesirably close to the cable jacket and/or shield which may adversely affect return loss, impedance and attenuation. These embodiments may also reduce the amount of material in
15 the center portion which may increase cable flexibility.

With reference to **Figure 8**, a communications cable **610** according to further embodiments of the present invention will now be described. The communications cable **610** includes a cable jacket **612**, a spacer **614**, a plurality of twisted pairs of insulated conductors **620**, **622**, **624**, **626**, a shield **616** and a
20 plurality of compartments **640**, **642**, **644**, **646**. It will, however, be understood that the shield **616** may be omitted. The cable jacket **612**, the plurality of twisted pairs of insulated conductors **620**, **622**, **624**, **626**, the shield **616** and the plurality of compartments **640**, **642**, **644**, **646** may generally be constructed in the same manner as the cable jacket **10**, the plurality of twisted pairs of insulated conductors
25 **20**, **22**, **24**, **26**, the shield **16** and the plurality of compartments **40**, **42**, **44**, **46** described above with reference to the communications cable **10**. Accordingly, a detailed description thereof need not be repeated.

As shown in **Figure 8**, the spacer **614** is situated within and is longitudinally coextensive with the cable jacket **612**. The spacer **614** may
30 comprise the same materials and may be fabricated using the same fabrication techniques that were discussed in connection with the spacer **14**. As illustrated in **Figure 8**, the spacer **614** includes a longitudinally extending center portion **630** and a plurality of longitudinally extending wall portions **632**, **634**, **636**, **638** radiating from the center portion **630**. Each individual wall portion **632**, **634**, **636**,

638 preferably includes plurality of radial sections **638a**, **638b**, **638c** wherein each individual radial section **638a**, **638b**, **638c** may be of constant thickness, or may increase in thickness or decrease in thickness with distance from the center portion **630**. As will be understood to one of skill in the art, the change in thickness of the radial sections that increase or decrease in thickness may be linear or non-linear, and may be continuous or discontinuous. In the embodiment illustrated in **Figure 8**, each wall portion **632**, **634**, **636**, **638** includes three radial sections **638a**, **638b**, **638c** which are configured such that the middle radial section **638b** is thinner than the other two radial sections **638a**, **638c** thus forming a recessed portion.

Alternatively, the embodiment illustrated in **Figure 8** may also be described as including two radial sections **638d**, **638e**, one that decreases in thickness in a discontinuous manner **638d** with distance from the center portion **630** and one that increases in thickness in a discontinuous manner **638e** with distance from the center portion **630**, which are configured such that the wall portions **632**, **634**, **636**, **638** have a recessed portion.

As will be understood by one of skill in the art, the width **A** of a recessed portion for any one wall portion **632**, **634**, **636**, **638** may be the same as or may vary from the width **A** of a recessed portion for any other wall portion **632**, **634**, **636**, **638**. It will also be understood that there may be multiple recessed portions.

These embodiments may allow for better control of the location of the twisted pairs within the compartments which may provide better separation between the twisted pairs which, in turn, may improve crosstalk performance at the possible expense of adversely affecting return loss. These embodiments may also use more material which may decrease cable flexibility, and may increase the probability that the wall portions will fold over which may allow the twisted pairs to slip into an adjoining compartment.

It will be understood that the various geometric shapes (*e.g.*, sawtooth shaped, knob shaped etc.) of the wall portions of the embodiments of the present invention illustrated in **Figures 1-8** may be combined. For example, the knob shaped cross-section illustrated in **Figure 6** may be combined with the recessed shaped cross-section in **Figure 8** to form wall portions having both a recessed portion and a knob shaped portion. It will also be understood that a conventional rip cord and/or a drain wire may be included in any of the embodiments of the present invention.

Communications cables according to embodiments of the invention in operation may reduce, and preferably minimize, cross-talk between the twisted pairs of insulated conductors. Moreover, communications cables according to embodiments of the invention may reduce, and preferably minimize, capacitance
5 imbalance as desired for such cables.

The foregoing is illustrative of the present invention and is not to be construed as limiting thereof. Although a few exemplary embodiments of this invention have been described, those skilled in the art will readily appreciate that many modifications are possible in the exemplary embodiments without materially
10 departing from the novel teachings and advantages of this invention. Accordingly, all such modifications are intended to be included within the scope of this invention as defined in the claims. It is to be understood that the foregoing is illustrative of the present invention and is not to be construed as limited to the specific embodiments disclosed, and that modifications to the disclosed
15 embodiments, as well as other embodiments, are intended to be included within the scope of the appended claims. The invention is defined by the following claims, with equivalents of the claims to be included therein.

THAT WHICH IS CLAIMED:

1. A communications cable comprising:
a cable jacket;
a spacer extending within the cable jacket, the spacer having a
longitudinally extending center portion and plurality of longitudinally extending
5 wall portions radiating from the center portion, the longitudinally extending wall
portions increasing in thickness from the center portion to the cable jacket, the
spacer and the cable jacket defining a plurality of compartments within the cable
jacket;
a shield extending between the spacer and the cable jacket; and
10 a twisted pair of insulated conductors disposed in one of the plurality of
compartments.
2. The communications cable according to Claim 1 further comprising
a plurality of twisted pairs of insulated conductors disposed in respective ones of
the plurality of compartments.
3. The communications cable according to Claim 2 wherein each of
the plurality of twisted pairs of insulated conductors has a different lay length.
4. The communications cable according to Claim 2 wherein the
plurality of longitudinally extending wall portions are configured so as to define a
plurality of compartments of a helical configuration within the cable jacket and the
plurality of twisted pairs of insulated conductors located within the plurality of
5 compartments extend helically about the longitudinal axis of the cable.
5. A communications cable comprising:
a cable jacket;
a spacer extending within the cable jacket, the spacer having a
longitudinally extending center portion and plurality of longitudinally extending
5 wall portions radiating from the center portion, the longitudinally extending wall
portions increasing in thickness over only a portion thereof from the center portion
to the cable jacket, the spacer and the cable jacket defining a plurality of
compartments within the cable jacket; and

10 a twisted pair of insulated conductors disposed in one of the plurality of compartments.

6. The communications cable according to Claim 5 further comprising a plurality of twisted pairs of insulated conductors disposed in respective ones of the plurality of compartments.

7. The communications cable according to Claim 6 wherein each of the plurality of twisted pairs of insulated conductors has a different lay length.

8. The communications cable according to Claim 7 wherein the plurality of longitudinally extending wall portions are configured so as to define a plurality of compartments of a helical configuration within the cable jacket and the plurality of twisted pairs of insulated conductors located within the plurality of
5 compartments extend helically about the longitudinal axis of the cable.

9. A communications cable comprising:
a cable jacket;
a spacer extending within the cable jacket, the spacer having a longitudinally extending center portion and plurality of longitudinally extending
5 wall portions radiating from the center portion, the longitudinally extending wall portions decreasing in thickness over only a portion thereof from the center portion to the cable jacket, the spacer and the cable jacket defining a plurality of compartments within the cable jacket; and
a twisted pair of insulated conductors disposed in one of the plurality of
10 compartments.

10. The communications cable according to Claim 9 further comprising a plurality of twisted pairs of insulated conductors disposed in respective ones of the plurality of compartments.

11. The communications cable according to Claim 10 wherein each of the plurality of twisted pairs of insulated conductors has a different lay length.

12. The communications cable according to Claim 11 wherein the plurality of longitudinally extending wall portions are configured so as to define a plurality of compartments of a helical configuration within the cable jacket and the plurality of twisted pairs of insulated conductors located within the plurality of
5 compartments extend helically about the longitudinal axis of the cable.

13. A communications cable comprising:
a cable jacket;
a spacer extending within said cable jacket, the spacer having a longitudinally extending center portion and plurality of longitudinally extending
5 wall portions radiating from said center portion, the longitudinally extending wall portions having a first radial section that increases in thickness with distance from the center portion and a second radial section that decreases in thickness with distance from the center portion, the spacer and the cable jacket defining a plurality of compartments within the cable jacket; and
10 a twisted pair of insulated conductors disposed in at least one of the compartments.

14. The communications cable according to Claim 13 wherein the first radial section is located between the center portion and the second radial section.

15. The communications cable according to Claim 13 wherein the second radial section is located between the center portion and the first radial section.

16. The communications cable according to Claim 13 wherein the first radial section and the second radial section are configured such that the plurality of longitudinally extending wall portions have a convex shaped cross-section.

17. The communications cable according to Claim 16 wherein the convex shaped cross-section is arcuate.

18. The communications cable according to Claim 16 wherein the convex shaped cross-section comprises a plurality of faces.

19. The communications cable according to Claim 13 wherein the first radial section and the second radial section are configured such that the plurality of longitudinally extending wall portions have a concave shaped cross-section.

20. The communications cable according to Claim 19 wherein the concave shaped cross-section is arcuate.

21. The communications cable according to Claim 19 wherein the concave shaped cross-section comprises a plurality of faces.

22. The communications cable according to Claim 13 wherein the first radial section and second radial section are configured such that the plurality of longitudinally extending wall portions have a recessed portion.

23. The communications cable according to Claim 13 wherein the first radial section and second radial section are configured such that the plurality of longitudinally extending wall portions have a ribbed portion.

24. The communications cable according to Claim 13 wherein the first radial section and the second radial section are configured such that the plurality of longitudinally extending wall portions have a sawtooth shaped cross-section.

25. A communications cable comprising:
a cable jacket;

a spacer extending within said cable jacket, the spacer having a longitudinally extending center portion and plurality of longitudinally extending wall portions radiating from said center portion, the longitudinally extending wall portions including a first section having a first thickness, a second section having a second thickness and a third section having a third thickness, the third thickness being different from the first and second thickness, the third section located between the first section and the second section, the spacer and the cable jacket defining a plurality of compartments within the cable jacket; and

a twisted pair of insulated conductors disposed in at least one of the compartments.

26. The communications cable of Claim 25 wherein the first, second and third thickness are different from one another.

27. The communications cable of Claim 25 wherein the first thickness and the second thickness are the same and the third thickness is different from the first thickness.

28. The communications cable of Claim 27 wherein the third thickness is greater than the first thickness.

29. The communications cable of Claim 27 wherein the third thickness is less than the first thickness.

30. A communications cable comprising:

a cable jacket;

a spacer extending within said cable jacket, the spacer having a longitudinally extending center portion and plurality of longitudinally extending wall portions radiating from said center portion, the longitudinally extending wall portions having a sawtooth shaped cross-section including a plurality of teeth, each tooth having a tooth height and a tooth spacing, the spacer and the cable jacket defining a plurality of compartments within the cable jacket; and

5 a twisted pair of insulated conductors disposed in at least one of the
10 compartments.

31. The communications cable according to Claim 30 wherein each tooth height is the same.

32. The communications cable according to Claim 30 wherein at least two tooth heights are different.

33. The communications cable according to Claim 30 wherein each tooth spacing is the same.

34. The communications cable according to Claim 30 wherein at least two tooth spacings are different.

35. The communications cable according to Claim 30 wherein at least two tooth heights are different and at least two tooth spacings are different.

36. A communications cable comprising:

a cable jacket;

5 a spacer extending within said cable jacket, the spacer having a longitudinally extending center portion and plurality of longitudinally extending wall portions radiating from said center portion, the longitudinally extending wall portions including a knob shaped cross-section, the spacer and the cable jacket defining a plurality of compartments within the cable jacket; and

a twisted pair of insulated conductors disposed in at least one of the compartments.

37. The communications cable according to Claim 36 wherein the knob shaped cross-section is a half knob.

38. The communications cable according to Claim 36 wherein the knob shaped cross-section is a whole knob.

38. The communications cable according to Claim 36 wherein the longitudinally extending wall portions includes a plurality of knob shaped cross-sections.

40. A communications cable comprising:

a cable jacket;

5 a spacer extending within said cable jacket, the spacer having a longitudinally extending center portion and plurality of longitudinally extending wall portions radiating from said center portion, the longitudinally extending wall

portions having a convex shaped cross-section, the spacer and the cable jacket defining a plurality of compartments within the cable jacket; and

a twisted pair of insulated conductors disposed in at least one of the compartments.

41. The communication cable of Claim 40 wherein the convex shaped cross-section is arcuate.

42. The communications cable of Claim 40 where the convex shaped cross-section comprises a plurality of faces.

43. A communications cable comprising:

a cable jacket;

5 a spacer extending within said cable jacket, the spacer having a longitudinally extending center portion and plurality of longitudinally extending wall portions radiating from said center portion, the longitudinally extending wall portions having a concave shaped cross-section, the spacer and the cable jacket defining a plurality of compartments within the cable jacket; and

a twisted pair of insulated conductors disposed in at least one of the compartments.

44. The communication cable of Claim 43 wherein the concave shaped cross-section is arcuate.


45. The communications cable of Claim 43 where the concave shaped cross-section comprises a plurality of faces.

COMMUNICATIONS CABLES WITH ISOLATORS

Abstract of the Disclosure

Communications cables are provided which utilize a cable jacket, twisted pairs of insulated conductors of insulated conductors, and a spacer separating the twisted pairs of insulated conductors. The spacer extends within the cable jacket and has a longitudinally extending center portion and a plurality of wall portions radiating from the center portion thereby defining a plurality of compartments within the cable jacket. In various embodiments of the present invention, the plurality of wall portions include a plurality of radiating sections with varying geometric shapes. The twisted pairs of insulated conductors are disposed in the compartments which may reduce crosstalk in the communications cable.

FIG. 1
FIG. 2
FIG. 3
FIG. 4
FIG. 5
FIG. 6
FIG. 7
FIG. 8
FIG. 9
FIG. 10
FIG. 11
FIG. 12
FIG. 13
FIG. 14
FIG. 15
FIG. 16
FIG. 17
FIG. 18
FIG. 19
FIG. 20
FIG. 21
FIG. 22
FIG. 23
FIG. 24
FIG. 25
FIG. 26
FIG. 27
FIG. 28
FIG. 29
FIG. 30
FIG. 31
FIG. 32
FIG. 33
FIG. 34
FIG. 35
FIG. 36
FIG. 37
FIG. 38
FIG. 39
FIG. 40
FIG. 41
FIG. 42
FIG. 43
FIG. 44
FIG. 45
FIG. 46
FIG. 47
FIG. 48
FIG. 49
FIG. 50
FIG. 51
FIG. 52
FIG. 53
FIG. 54
FIG. 55
FIG. 56
FIG. 57
FIG. 58
FIG. 59
FIG. 60
FIG. 61
FIG. 62
FIG. 63
FIG. 64
FIG. 65
FIG. 66
FIG. 67
FIG. 68
FIG. 69
FIG. 70
FIG. 71
FIG. 72
FIG. 73
FIG. 74
FIG. 75
FIG. 76
FIG. 77
FIG. 78
FIG. 79
FIG. 80
FIG. 81
FIG. 82
FIG. 83
FIG. 84
FIG. 85
FIG. 86
FIG. 87
FIG. 88
FIG. 89
FIG. 90
FIG. 91
FIG. 92
FIG. 93
FIG. 94
FIG. 95
FIG. 96
FIG. 97
FIG. 98
FIG. 99
FIG. 100






FIG. 2.




FIG. 5.




FIG. 6.




FIG. 7.




FIG. 8.